RCT

Open cooling towers







Key benefits

- Easy maintenance
- Superior construction
- Low height

Configuration

Counter flow

Fans system

Axial fan, induced draft

Capacity range

7 - 265 l/s

Water distribution

Pressurised

Maximum entering water temperature

55°C standard fill
60°C with alternative fill

Typical applications

- Small to medium industrial applications
- Dirty water applications
- Replacement of field erected towers with basinless units

This file has been generated from the BAC website on: 28/03/2024
For more up to date information, visit: https://www.baltimoreaircoil.eu/en/products/RCT

Easy maintenance

- Easy **basin access** from all sides.
- Easy no-tool **removal of side panel** gives access to all internal cooling tower components.
- **Sloped basin** to flush out dirt and debris.
- **Easy removable** fill, spray branch arms, eliminators and combined inlet shields.
- Easy **access to motor and drives** from outside.

Superior construction

- Superior structure strength: **pultruded composite construction** guarantuees a long service life.

Low height

- Counterflow cooling tower with very restricted height, fits **in most enclosures**.

Interested in the RCT cooling tower for cooling your process water? Contact your local BAC representative for more information.

Downloads

- RCT open cooling towers
- RCT Open cooling towers

This file has been generated from the BAC website on: 28/03/2024
For more up to date information, visit: https://www.baltimoreaircoil.eu/en/products/RCT