



CXVE 1212-1218

Refrigerant condensers

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

Last update: 24/04/2024

CXVE 1212-1218



1. Refrigerant in; 2. Refrigerant out; 3. Make up; 4. Overflow; 5. Drain; 6. Access door.

Model	Weights (kg)			Dimensions (mm)			Air Flow (m³/s)	Fan Motor (kW)	Water Flow (l/s)	Pump Motor (kW)	R717 charge (kg)
	Oper. Weight (kg)	Ship. Weight(kg)	Heaviest Section (kg)	L	W	H					
CXVE 268-12 12-20L	8930	5570	3200	3651	3607	5199	41.7	(2x) 7.5	54.6	(1x) 5.5	80.0
CXVE 287-12 12-30L	8980	5630	3260	3651	3607	5199	47.1	(2x) 11.0	54.6	(1x) 5.5	80.0
CXVE 302-12 12-20L	9810	6410	4030	3651	3607	5199	40.8	(2x) 7.5	54.6	(1x) 5.5	133.0
CXVE 341-12 12-40L	9940	6540	4160	3651	3607	5199	51.2	(2x) 15.0	54.6	(1x) 5.5	133.0
CXVE 341-12 12-20L	11000	7540	5420	3651	3607	6080	40.2	(2x) 7.5	54.6	(1x) 5.5	186.0
CXVE 343-12 12-20L	10690	7260	5140	3651	3607	6080	40.4	(2x) 7.5	54.6	(1x) 5.5	160.0
CXVE 356-12 12-20L	11390	7920	5800	3651	3607	6080	40.0	(2x) 7.5	54.6	(1x) 5.5	200.0
CXVE 356-12 12-30L	10610	7180	5060	3651	3607	6080	45.6	(2x) 11.0	54.6	(1x) 5.5	160.0
CXVE 363-12 12-20L	12010	8500	6380	3651	3607	6080	39.6	(2x) 7.5	54.6	(1x) 5.5	240.0
CXVE 369-12 12-30L	11050	7590	5480	3651	3607	6080	45.4	(2x) 11.0	54.6	(1x) 5.5	186.0
CXVE 379-12 12-40L	10680	7250	5130	3651	3607	6080	50.8	(2x) 15.0	54.6	(1x) 5.5	160.0
CXVE 381-12 12-30L	11920	8410	6290	3651	3607	6080	44.7	(2x) 11.0	54.6	(1x) 5.5	240.0
CXVE 393-12 12-30L	12050	8540	6420	3651	3607	6080	44.7	(2x) 11.0	54.6	(1x) 5.5	240.0
CXVE 394-12 12-40L	10820	7380	5270	3651	3607	6080	50.8	(2x) 15.0	54.6	(1x) 5.5	160.0
CXVE 411-12 12-40L	11520	8050	5930	3651	3607	6080	50.2	(2x) 15.0	54.6	(1x) 5.5	200.0
CXVE 420-12 12-40L	12120	8610	6490	3651	3607	6080	49.8	(2x) 15.0	54.6	(1x) 5.5	240.0
CXVE 438-12 18-30L	14010	8890	5300	5480	3607	5349	63.6	(3x) 7.5	85.2	(1x) 7.5	160.0
CXVE 460-12 18-30L	14670	9510	5930	5480	3607	5349	64.2	(3x) 7.5	85.2	(1x) 7.5	200.0
CXVE	14130	9010	5420	5480	3607	5349	71.8	(3x)	85.2	(1x)	160.0

466-12 18-45L								11.0		7.5	
CXVE 490-12 18-45L	14800	9630	6050	5480	3607	5349	72.5	(3x) 11.0	85.2	(1x) 7.5	200.0
CXVE 491-12 18-60L	14230	9110	5520	5480	3607	5349	80.0	(3x) 15.0	85.2	(1x) 7.5	160.0
CXVE 504-12 18-30L	15740	10530	7320	5480	3607	6230	62.5	(3x) 7.5	85.2	(1x) 7.5	240.0
CXVE 525-12 18-30L	15870	10670	7460	5480	3607	6230	62.5	(3x) 7.5	85.2	(1x) 7.5	240.0
CXVE 543-12 18-45L	15860	10660	7440	5480	3607	6230	68.6	(3x) 11.0	85.2	(1x) 7.5	240.0
CXVE 545-12 18-30L	16910	11640	8430	5480	3607	6230	61.8	(3x) 7.5	85.2	(1x) 7.5	300.0
CXVE 563-12 18-45L	15990	10790	7580	5480	3607	6230	70.6	(3x) 11.0	85.2	(1x) 7.5	240.0
CXVE 574-12 18-60L	15960	10750	7540	5480	3607	6230	75.6	(3x) 15.0	85.2	(1x) 7.5	240.0
CXVE 601-12 18-45L	17950	12630	9420	5480	3607	6230	69.0	(3x) 11.0	85.2	(1x) 7.5	360.0
CXVE 601-12 18-60L	16090	10890	7680	5480	3607	6230	78.5	(3x) 15.0	85.2	(1x) 7.5	240.0
CXVE 628-12 18-60L	17130	11870	8650	5480	3607	6230	77.6	(3x) 15.0	85.2	(1x) 7.5	300.0
CXVE 643-12 18-60L	18050	12730	9520	5480	3607	6230	76.8	(3x) 15.0	85.2	(1x) 7.5	360.0